

## Jotafloor Non Slip Aggregate

### Product description

This is graded silica aggregates, designed to be spread into a desired non-skid system. Available in coarse, medium and fine particle sizes. Suitable as anti-skid material in a wide range of coating systems in atmospheric environments. Suitable on any type of surface, depending on the specific coating system.

### Typical use

Recommended for warehouses, garages, dairies, factories, laboratories, aircraft hangars, food, beverage and plant rooms where non-slip properties are required. The spreading is to take place in the wet film during application.

### Product data

Property	Test/Standard	Description
Solids by volume	ISO 3233	100 %
VOC-Solvent Emission Directive	SED (1999/13/EC)	0 g/kg

The provided data is typical for factory produced products, subject to slight variation depending on colour.

### Product mixing ratio (by volume)

Single pack

### Additional information

If required Jotafloor Non Slip Aggregate can be used with Jotafloor Topcoat, Jotafloor Coating and Jotafloor SL Universal. (Advice should be sought from your local Jotun office regarding application techniques as these vary slightly from product to product).

Jotafloor Non Slip Aggregate is cast on to the wet first coat of the Jotafloor material until the whole surface is covered. Distribute the product from a container eg. distribution sieve, that will allow the aggregate to fall directly onto the wet coating.

Once the first coat has dried, remove the excess aggregate from the surface by vacuum or sweeping. The aggregate can be reused if clean.

Apply the final coat of Jotafloor material to the desired thickness.

### Packaging (typical)

	Volume
Jotafloor Non Slip Aggregate	25 kg

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

---

## Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

### Shelf life at 23 °C

Jotafloor Non Slip Aggregate 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

---

## Caution

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

---

## Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

---

## Colour variation

Products primarily meant for use as primers and antifoulings may have slight color variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

---

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.