



Autotrans Fluid BW is an automatic transmission fluid which is specifically designed for BTR M85LE and M95LE automatic transmissions as fitted to Ford vehicles.

Autotrans Fluid BW provides good antiwear, rust and corrosion protection, resistance to oxidation, control of deposit formation, retention of frictional characteristics and correct fluidity at all operating temperatures.

APPLICATIONS

Autotrans Fluid BW is specifically designed for:

- BTR M85LE four speed automatic transmissions fitted to 6 cylinder Series 2 Ford Falcon EA, Fairlane NA and LTD DA model passenger cars and subsequent models.
- BTR M95LE four speed automatic transmissions fitted to 8 and 6 cylinder Ford Falcon EB, Fairlane NC and LTD DC and subsequent models.

BENEFITS

- Has the correct frictional and lubricity properties to ensure good wear protection of critical components, quiet operation and smooth shifting.
- Has a high viscosity index to ensure efficient operation at low temperature and retain viscosity at operating temperature.
- Has good oxidation stability to inhibit sludge formation or thickening at high operating temperature.
- Protects against rust and corrosion.
- Compatible with sealing materials.
- Dyed red for identification.

PERFORMANCE STANDARDS

Suitable for use where fluids meeting BTR 5M-52 are recommended.

TYPICAL CHARACTERISTICS

| | |
|-------------------------|-------|
| Product Code | 1275 |
| Density at 15°C, kg/L | 0.877 |
| Colour | Red |
| Flash Point, COC °C | 218 |
| Pour Point, °C | -39 |
| Viscosity, cSt at 40°C | 38.0 |
| Viscosity, cSt at 100°C | 7.0 |
| Viscosity Index | 149 |



PACK SIZES

205L, 60L, 20L, 1L

ENVIRONMENT, HEALTH and SAFETY

Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

OTHER INFORMATION

For further information on Caltex products and services call the Lubelink Advisory Service on 1300 364 169 between 8.00am and 6.00pm (EST) Monday to Friday.

Information in this publication is accurate at the time of printing and reasonable care has been taken to ensure it is complete and accurate. However, this information is subject to change (such as when formulations or usage and storage information changes). Please visit www.caltex.com.au for the latest product information. Independent advice should be sought before taking any action in reliance on the information in this publication, and Caltex Australia Limited and its related bodies corporate accept no liability for any reliance on this publication's content.